

Shower Base

SPECIFICATIONS

Non-Slip Floor Construction: Proprietary high-performance polymer/mineral blend (Partial list of disclosed materials: Acrylic modified polyester, NPG-isophthalic resin, > 60% minerals & lightweight microsphere blend, more ...)

Floor Color: White, Biscuit, Almond, Grey

Threshold: Genuine Corian® or LG HI-MACS® Solid Surface, 3"x3" (Other sizes and zero-entry available).

Finish: Matte

Dimensions: Up to 114" Long x 80" Wide. Drain up to 57" from any wall – *almost* anywhere you'd want it.

Drain: 4 1/4" Cover, 3 1/4" Hole, Hardware not included.

Weight: Varies on Size. 60x36 Right Hand Drain ~100lbs

"Frameless" Perimeter: Note that walls come right to floor for an extra-clean look (see pic on right).

Thermal Shock: Over 2000+ Cycles! *3rd Party Tested.

(ANSI standard is 250 cycles of hot/cold water resistance)

Slip Resistance: > .42 Dynamic Coefficient of Friction.



FEATURES

- Fantastic slip resistant finish cleans easily.
- Sanitary, non-porous Surface.
- Will not harbor mold/mildew.
- Made in USA.
- Meets & Exceeds all ICPA & ANSI quality standards
- *IAPMO approved, has Universal Plumbing Code, Certificate #7499

**Pan dimensions vary +/- 1/8"*

SUGGESTED DRAINS

- Sioux Chief Mfg. Model: 825-2P - PVC
- Oatey part number: 42025 - PVC
- Oatey part number: 42150 - PVC
- Kohler Model: K9132 Stainless.

***Drain Not Included**

Visual Example Of The Water Dams

The invisible water dams are a hearty 1/4" thick ABS. They are conveniently fitted on the jobsite and seemingly impossible to fail in the field. We've never yet heard of a break or crack or damage-caused water breach in these dams in over 20 years of nationwide service with tens of thousands of shower floors installed. As shown, they are installed behind the walls, which should come all the way to the floor. An installation video is provided to all installers.

